

METHOD AND APPARATUS FOR DYNAMICALLY
CONTROLLING SCROLLER SPEED EMPLOYED FOR A USER
INTERFACE OF A WEARABLE APPLIANCE

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates generally to mobile computing devices such as personal digital assistants (PDAs), cellular phones, pagers, and the like, and more specifically, to a wearable device/appliance (e.g., a wrist watch) capable of wirelessly accessing information and equipped with an interactive user interface and high-resolution display including a scroll device implementing dynamic speed control for enabling seamless fine-grain and coarse-grain scroll and/or cursor movement through displayed content without notice to the user of the scroll device.

Discussion of the Prior Art

Computing, mobile and wireless communications technologies have been rapidly advancing -culminating in a variety of powerful user friendly devices such as personal digital assistants (PDAs), cellular phones, pagers, etc. Today, it is possible to purchase handheld PDA's, e.g., palmtops such as the Palm Pilot®, that employ wireless communication devices and that combines computing, telephone/fax, and networking features. A typical PDA may function as a cellular phone, fax sender, and personal organizer and are pen-based, requiring a stylus for text entry. As such, these device incorporate handwriting recognition features and may even employ voice recognition technologies that react to voice input. Small devices such as the RIM 950 and the Motorola PageWriter 2000 pager use a small keyboard for input.

Today, the industry is striving to provide advancements by providing increased PC desktop-like functionality while both decreasing size and power requirements. More recently there have been attempts to incorporate some of the capabilities of the above devices into wrist watches. However, today, only special wearable watch devices are available that, besides time keeping functions, may possess a compass, or a Global Positioning System (GPS), or barometer, heart rate monitor, Personal Handy System (PHS) phone, pager, etc.. There are shortcomings in these existing special function watches in that most of them are bulky, are mostly unconnected the Internet or other PC/network devices, have limited battery life, and, are difficult to use. These currently available special function wrist watches additionally have user interfaces that are quite limited in what they can display. For example, in the context of setting time in digital watches, currently, the user is only enabled to set the hour and minute independently, with time only advancing in one direction. Furthermore, most of them have a 6 to 8 seven segment LED or LCDs which can be used to display 6 or 8 digits/letters, and have a small number of indicators that can display AM/PM, Alarm on/off, etc. only at fixed locations within the display. A few watches are currently appearing on the market that have slightly richer display characteristics. Regardless, these various shortcomings have to be solved, otherwise there is no compelling reason for these watches to become popular. The design of a wrist watch for mobile computing applications offers a significant challenge because the watch is a small device. That is, both fitting components and power supplies such as batteries into such a small volume and given the limited screen size of watches pose limitations that have be overcome. Solving these issues is worthy because the watch is an attractive form as 1) it is one of the few devices that a very large fraction of the population is

already accustomed to worldwide, 2) is accessible almost all the time, and, 3) is hard to lose.

It would thus be highly desirable to provide a wearable device/appliance (a wrist watch) capable of wirelessly accessing information and equipped with an interactive user interface and high resolution display for providing a variety of desktop PC-like functions.

It would additionally be highly desirable to provide a wearable device/appliance (a wrist watch) capable of wirelessly accessing information and equipped with an interactive user interface equipped with a scroll device, e.g., roller ball, wheel or dial-type controller, for enabling scrolling through text and graphics displayed via the user interface.

Moreover, it would additionally be highly desirable to provide a wearable device/appliance (a wrist watch) capable of wirelessly accessing information and equipped with an interactive user interface equipped with a scroll device implementing a dynamic scroll speed controller for reducing the amount of user manipulation of the scroller to get to a particular point in the display the user wants to get to, while retaining fine-grain control over positioning.

Summary of the Invention

It is an object of the present invention to provide a wearable device/appliance (a wrist watch) capable of wirelessly accessing information and equipped with an interactive user interface and high resolution display for providing a variety of desktop PC-like functions.

It is another object of the present invention to provide a wearable device/appliance (a wrist watch) capable of wirelessly accessing information and equipped with an interactive user interface including a scroll device implementing a dynamic scroll speed controller for enabling fine-grain and coarse-grain positioning of a scroll and/or cursor positioning of displayed content in a manner seamless to the user.

It is a further object of the present invention to provide a wearable device/appliance (a wrist watch) capable of wirelessly accessing information and equipped with an interactive user interface implementing a dynamic scroll device for enabling scrolling through text and graphics displayed via the user interface in a manner such that the amount of user manipulation of the scroller to get to a particular position in the display the user wants to get to is reduced, while retaining fine-grain control over positioning without needing excessive scroller manipulation.

According to the invention, there is provided a system and method for dynamically controlling scrolling functions of a display indicator provided in a wearable appliance that displays textual or graphical content, the appliance implementing a scroll device for generating scroll events in response to user manipulation thereof, the method comprising the steps of: receiving scroll events for incrementally advancing the indicator per scroll event in a first direction to provide fine-grain scroll indicator movement, and simultaneously tracking the advancing direction; determining a predetermined number of the fine-grain indicator increments in the first direction; and, thereafter, in response to continued receipt of scroll events, providing, in a manner that is seamless to a user, coarse-grain scroll indicator movement by advancing said indicator for a pre-determined number

of increments per scroll event in the first direction, the coarse-grain scroll indicator movement greater than the fine-grain scroll indicator movement, whereby fewer scroll device manipulations are required to achieve a desired scroll indicator position on the display.

Advantageously, such a method and system may be implemented for any application requiring large scrolling movements, including an application providing time-keeping and time-setting display functions where the scroll device is manipulated for controlling minute and hour-hand indicators.

Brief Description of the Drawings

Further features, aspects and advantages of the apparatus and methods of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

Figure 1 illustrates conceptually the wearable information access wrist watch device of the invention.

Figure 2 is a detailed block diagram illustrating the hardware architecture of the Wrist Watch device 10 implementing the dynamic scroll device of the present invention.

Figure 3 illustrates the software architecture 200 for the Wrist Watch device 10.

Figure 4 illustrates an example OLED system display 300 providing a main menu of selectable icons for launching Personal Information Management applications provided in the Wrist Watch device.

Figures 5(a) and 5(b) illustrates the Wrist Watch user interface 350 provided for performing alarm setting functions.

Detailed Description of the Preferred Embodiments

5

Figure 1 illustrates conceptually the wearable information access wrist watch device of the invention. Referred to herein as the "Wrist Watch" 10, the system looks like a regular watch but is capable of receiving information from adjunct devices such as a PC, a mobile computer, other pervasive devices being carried by the user and directly from a network via a wireless communications mechanism.

10

As shown in Figure 1, the Wrist Watch device 10 is based on a modular concept designed to include a motherboard or base card 20 of minimum card size that leverages state-of-the-art technologies as will be described in greater detail herein. Specifically, the base card 20 may be implemented in various types of shells 25a,...,25c for enabling various functions. For example, the base card 20 may be implemented in a basic shell 25a providing desktop like functionality via a touch screen display; a hands-free mobile shell 25b providing, in addition to basic desktop functionality, a communications interface with GPS and mobile phone communications capability etc., and including a touch screen display, scroll/pointing devices, and microphone and speaker devices; and an expanded function shell 25c, providing touch screen, buttons and support for various devices such as GPS/compass, thermometer, barometer, altimeter, etc.

25

30

Figure 2 is a detailed block diagram illustrating the hardware architecture of the Wrist Watch system 10. As shown in Figure 2, the base card 20 includes a first or main card 50 housing the core processing unit, I/O, and memory. For example the main card

50 includes a CPU 55, such as a Cirrus Logic CL-EP7211, which is a single-chip embedded controller functioning as a CPU for ultra-low-power applications, and armed with processing and enhanced memory management features to function equivalently as a 100 MHz Pentium. The core processing unit may operate at 2.5 V, and, to minimize the board size, may be equipped with a 3.68 MHz ceramic resonator 57 for generating the main frequency clock and timing signals. The main card 50 additionally includes sufficient nonvolatile and volatile memory including, for example, 64Mbit EDO DRAM 58 and SRAM/Flash memory 59 that supports the system code. One communications subsystem of the Wrist Watch 10 includes a line of sight Infrared Data Association (IrDA) communications interface having a low-power IR transceiver module 60 mounted on the card 50 for direct connection with interface decoder pins of the CPU 55 which includes an IrDA SIR protocol encoder. The first card 50 additionally includes various Analog to Digital converters (ADC), memory refresh logic and industry standard interfaces such as a compact flash interface for example, so that other devices could be attached to the Wrist Watch 10. Other interfaces such as Universal Serial Bus (USB), and I2C, etc. may additionally be incorporated. Figure 2 further illustrates the main card 50 as comprising power supply subsystem including a rechargeable Li-Polymer type battery 65 and a DC to DC converter 66 for supporting a wide dynamic range of Wrist Watch system/sub-system load.

With further reference to Figure 2, the main card 50 has no audio capability but is equipped with a PCM audio interface in expansion tabs (not shown) for an accessory card, i.e., either card 75 or 80, in the expanded-shell Wrist Watch designs that support PCM audio. Particularly, the accessory card 75, 80 implemented includes a speaker and a microphone combination 77, 83 respectively, with the microphone functioning to record voice

input which may be processed by the processor subsystem or stored in a storage subsystem for subsequent playback, and the speaker functioning to provide voice output, produce customized tones, and enable acoustic coupling with other listening devices, etc.

5 As shown in Figure 2, each speaker/microphone combination 77. 83 is connected to a respective pulse-coded modulation PCM coder/encoder devices (CODECs) 78, 84 which are controlled by a respective PCM interface 79,89 to the CPU 55. The accessory card 75, 80 is additionally equipped with various communications
10 subsystems including low power and intermediary power radio frequency communications devices that support a Wireless Application Protocol ("WAP") used to provide communications links to mobile computers, mobile phones, portable handheld devices and, connectivity to the Internet. In one embodiment, the specific communications subsystems include circuitry for supporting Bluetooth 81 or like small-factor, low-cost radio solution circuitry, e.g., an RF-modem 76, and may include other low power radio and Flex-paging communications circuits (not shown), etc. For instance, as shown in Figure 2, the auxiliary
20 communication card 80 implements the Bluetooth industry standard for Radio Frequency (RF) communication, however, it is understood that other standards such as IEEE 802.11 or other RF protocols may be implemented as well. Moreover, portions of these communication protocols may be implemented on the processor on
25 the main board 50 so that the total number of the components required is minimized. The CPU system on the main card 50 preferably employs a first Universal Asynchronous Receiver Transmitter (UART1) device (not shown) for supporting either the RF-modem 76 or Bluetooth 81 communications functionality and, may
30 be equipped with a second UART device (UART2) providing support for data download functionality, e.g., from a PC or network server. It is understood that any like data transfer mechanism

or data exchange interface device may be implemented to provide data download and RF communications support functionality.

5
a1
10
15
20
25
30

For purposes of interacting with the device, the Wrist Watch system 10 is provided with a touch sensitive screen/panel 90 shaped within a standard watch form factor, and also a roller wheel mechanism, i.e., jog encoder 95. The touch sensitive screen enables the direct launching of applications by physical user entry of a graffiti "squiggle" in the manner such as described in commonly-owned co-pending U.S. Patent Application No. _____ [YOR92000-0234, Atty. Docket No. 13577] entitled GRAFFITI BASED APPLICATION LAUNCH ON A SMART WATCH, the whole contents and disclosure of which is incorporated by reference as if fully set forth herein, and may initiate other applications/actions/events by physical touching of certain Wrist Watch display areas. In one embodiment, the touch sensitive screen panel is provided with a four (4) position touch screen. For instance, forward and back navigation for Wrist Watch displays is enabled by physically touching certain areas of the touch sensitive panel. The roller wheel mechanism 95 may be rolled up or down (i.e., clockwise or anticlockwise) to simulate a display cursor scrolling function for text and graphics. For example, in the context of the present invention, the roller wheel mechanism 95 generates signals that are A/D converted for receipt by the processor to enable movement of the Wrist Watch display cursor, and more particularly, movement of displayed minute hand and hour hand indicators for setting of various alarms and time-keeping functions provided by the Wrist Watch system. Preferably, when the wheel mechanism moves by more than a predetermined amount, e.g., 20° degrees, the wheel generates a signal as a mouse device would when rolled. If a user rolls the wheel continuously, the wheel generates a signal for every 20 degrees of rotation (hereinafter "rotation event(s)"), with the

21
con
5 event generated including an indication specifying whether the wheel was turned clockwise or anticlockwise. In this manner, the direction of the roller wheel, and consequently, the direction of cursor movement through a particular display, is tracked by the processor. The roller wheel mechanism additionally may be pushed or depressed to generate a signal (hereinafter "wheel click event(s)"), akin to a keypress or mouse click event, for activating a selected application, hyperlink or a menu item. In an alternate embodiment, the roller device may comprise a bezel
10 which may be rotated and depressed for generating rotation and wheel click events respectively, such as described in commonly-owned co-pending U.S. Patent Application No. _____ [YOR92000-0235, Atty. Docket No. 13578] entitled BEZEL BASED USER INTERFACE FOR A SMART WATCH, the whole contents and disclosure of which is incorporated by reference as if fully set forth herein. It is understood that other types of scroll device may be implemented to provide cursor movement, e.g., a slider. Moreover, a standard button may be implemented for providing selection functions.

20 As further shown in Figure 2, various Analog to Digital converters (ADC) 68 support an interface with the touch screen display panel 90, and an interface with the jog encoder or button for the roller wheel mechanism 95. An interface 69 is provided for a unit 98 housing a high resolution (VGA equivalent) emissive
25 Organic Light Emitting Diode (OLED) high contrast display 100. Further, the main card 50 for the basic shell interfaces to a buzzer 63 controlled directly by the CPU 55 using its buzzer interface and timer counters. To detect the posture of the watch, a mechanical four-way tilt sensor 72 is further provided
30 comprising mechanical switches (for detecting degree of tilt) producing signals which may be detected by the CPU. This sensor may be used for the various purposes such as power management, display control, etc. In a preferred embodiment, additional

sensors may be attached to the Wrist Watch device over an interface. Examples may include additional tilt and motion (velocity, direction, speed) sensors, environment sensors such as thermal sensors, pressure sensors, health monitoring sensors such as blood pressure, etc. The Wrist Watch accordingly provides the display for the sensor and may also analyze the data collected from the sensors.

With more particularity, the high contrast display 100 of Figure 2 does not need a backlight to make the display visible. Thus, the power consumed by the display is proportional to the number of pixels that are turned on in the display. Since the pixels preferably comprise light emitting diodes, the display is automatically visible at night and a user does not need to press any buttons to see the display. Moreover, the OLED display 100 may be viewed clearly at a wide variety of angles with the brightness of these displays being controlled by limiting the amount of current supplied to the diodes. In one embodiment, the OLED chip 100 is a high-resolution pixel addressable display, e.g., 640x480, for enabling the display of various textual and graphical items on the watch face, similar to what may be displayed on a computer screen or a Palm Pilot®. For example, the time may be represented by drawing the hour and minute hands on a watchface display. Further, the hands of the watchface display may be erased when, at some other time, a display of a photograph is desired to be displayed.

Figure 3 illustrates the software architecture 200 for the Wrist Watch device 10. At its lowest level, the Wrist Watch system runs an operating system 210, e.g., LINUX 2.2.1, that permits multiple user level and kernel level threads to run and will support multitasking and multi-user support. Device drivers are provided for each input/output subsystem will handle low level

device dependent code and interfaces so that higher level Application Programming Interfaces (APIs) can be implemented on top of them. The device drivers provided for each input/output subsystem include a serial I/O system driver 212, IrDA system driver 214, RF-Modem subsystem driver 216, Bluetooth system driver 218, flash memory 220, touch screen subsystem driver 222, LCD subsystem driver 224, OLED subsystem driver 226, roller wheel subsystem driver 228 and tilt sensor device driver 229. A client-server graphics subsystem 230, storage subsystem manager 240 and synchronization sub-system manager 250 is provided on top of the device drivers for receiving and transmitting I/O events between the applications, updating of the screen, etc. A graphics library is available for the application writer so that custom screens may be displayed. A user interface manager 255 is provided to process events received from user input devices such as the roller wheel (jog encoder) and touch panel for the appropriate applications. A communication subsystem manager 260 is provided to handle events from communication channels and pass the events to the right application to set things up for data transfers to proceed. The synchronization manager 250 is provided to synchronize data between the Wrist Watch and the other devices. Particularly, it receives the data from the communication channel and operates in conjunction with the right application to decode the sent data and update the data for the application receiving the data. An example of this would be an update to a calendar event. A system wide power manager 270 is provided to monitor and control power consumption on the device and communicate with other subsystems such as the operating system scheduler to optimize the battery life of the device. The power manager 270, for example, measures the power left in the battery, estimates the power required to run an application, and recommends what subsystems need to be shut down as the battery starts draining out.

As further shown in Figure 3, the Wrist Watch device 10 is equipped with Wrist Watch shell application software 275 provided on top of the basic graphics, communication and synchronization subsystems. One key application supported is the microbrowser which enables access to a WAP-supporting Web site and receives Web-based communications written in, for example, the Wireless Markup Language ("WML") using the XML standard. WML particularly is designed to optimize Internet text data for delivery over limited-bandwidth wireless networks and onto small device screens, and particularly, is devised to support navigation with limited input mechanisms, e.g., buttons. Details regarding the implementation of WML in the Wrist Watch device may be found in commonly-owned, co-pending U.S. Patent Application No. [YOR92000-0224, Atty. Docket No. 13574] entitled SYSTEM AND METHOD EMPLOYING WML ANNOTATIONS FOR USER INTERFACE CONTROL OF A WEARABLE APPLIANCE the contents and disclosure of which is incorporated by reference as if fully set forth herein. Other supported applications include Personal Information Management (PIM) applications software 280. Figure 4 illustrates an example system display 300 providing a main menu 302 comprising selectable icons for launching the following PIM applications: an icon 310 for launching an application directed to displaying/maintaining "to do" lists, an icon 312 for launching an application directed to displaying/maintaining calendars and appointments, an icon 314 for launching an application directed to retrieving/storing/displaying e-mail messages, an icon 316 for launching an application directed to retrieving/storing/displaying digital photographs and bit-mapped images, an icon 318 for launching an application directed to retrieving/storing/displaying phone lists, an icon 320 for launching an application directed to setting of time and alarms which is shown highlighted and indicated by the displayed text

20
can.

5 "SET ALARMS", an icon 322 for launching an application directed to retrieving/storing/displaying comic images such as Dilbert® United Feature Syndicate, Inc., and, an icon 324 for launching an application directed to providing stop watch and elapsed time features. Other applications may include those enabling the receipt of excerpts of personalized data, such as traffic information, weather reports, school closings, stock reports, sports scores, etc., from the world wide web. These excerpts may be received as notifications or alarms on the Wrist Watch system

10 10. Inter-device interaction software applications are included to permit the watch display to become the display for another device such as a GPS located in a concealed location, (e.g., a bag), or a thermostat on the wall, etc. Thus, this application software enables communication between the other device and the Wrist Watch by receiving/displaying the data and transmitting back information sent from the Wrist Watch. As a further example, caller Id information may be displayed on the Wrist Watch display when the cell phone that belongs to that person rings. Typically, multiple persons are congregated in a room and carry their cell phones in a hand bag or wear them on their belts, have a hard time determining which cell phone is ringing when a ringing tone is heard in a room. This results in every person in the room pulling out his/her cell phone out of their handbag or belt to check if it is the one that is ringing. The

25 caller Id display feature of the Wrist Watch device is particularly advantageous as each wearer may simply glance at the watch and would immediately know if the ringing phone belonged to him/her, in addition, to determining who the calling party is facilitating the decision of whether or not he/she should answer the phone. In a further example, this application software may allow the data from the Wrist Watch storage subsystem 240 to be viewed on another device such as on a PDA, PC, and other community viewing devices. In the preferred embodiment,

30

10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780
1790
1800
1810
1820
1830
1840
1850
1860
1870
1880
1890
1900
1910
1920
1930
1940
1950
1960
1970
1980
1990
2000
2010
2020
2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
2130
2140
2150
2160
2170
2180
2190
2200
2210
2220
2230
2240
2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400
2410
2420
2430
2440
2450
2460
2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
2610
2620
2630
2640
2650
2660
2670
2680
2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
2850
2860
2870
2880
2890
2900
2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
3090
3100
3110
3120
3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320
3330
3340
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540
3550
3560
3570
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760
3770
3780
3790
3800
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
3990
4000
4010
4020
4030
4040
4050
4060
4070
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200
4210
4220
4230
4240
4250
4260
4270
4280
4290
4300
4310
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420
4430
4440
4450
4460
4470
4480
4490
4500
4510
4520
4530
4540
4550
4560
4570
4580
4590
4600
4610
4620
4630
4640
4650
4660
4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820
4830
4840
4850
4860
4870
4880
4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040
5050
5060
5070
5080
5090
5100
5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
5250
5260
5270
5280
5290
5300
5310
5320
5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
5490
5500
5510
5520
5530
5540
5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
5750
5760
5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960
5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
6190
6200
6210
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400
6410
6420
6430
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
6750
6760
6770
6780
6790
6800
6810
6820
6830
6840
6850
6860
6870
6880
6890
6900
6910
6920
6930
6940
6950
6960
6970
6980
6990
7000
7010
7020
7030
7040
7050
7060
7070
7080
7090
7100
7110
7120
7130
7140
7150
7160
7170
7180
7190
7200
7210
7220
7230
7240
7250
7260
7270
7280
7290
7300
7310
7320
7330
7340
7350
7360
7370
7380
7390
7400
7410
7420
7430
7440
7450
7460
7470
7480
7490
7500
7510
7520
7530
7540
7550
7560
7570
7580
7590
7600
7610
7620
7630
7640
7650
7660
7670
7680
7690
7700
7710
7720
7730
7740
7750
7760
7770
7780
7790
7800
7810
7820
7830
7840
7850
7860
7870
7880
7890
7900
7910
7920
7930
7940
7950
7960
7970
7980
7990
8000
8010
8020
8030
8040
8050
8060
8070
8080
8090
8100
8110
8120
8130
8140
8150
8160
8170
8180
8190
8200
8210
8220
8230
8240
8250
8260
8270
8280
8290
8300
8310
8320
8330
8340
8350
8360
8370
8380
8390
8400
8410
8420
8430
8440
8450
8460
8470
8480
8490
8500
8510
8520
8530
8540
8550
8560
8570
8580
8590
8600
8610
8620
8630
8640
8650
8660
8670
8680
8690
8700
8710
8720
8730
8740
8750
8760
8770
8780
8790
8800
8810
8820
8830
8840
8850
8860
8870
8880
8890
8900
8910
8920
8930
8940
8950
8960
8970
8980
8990
9000
9010
9020
9030
9040
9050
9060
9070
9080
9090
9100
9110
9120
9130
9140
9150
9160
9170
9180
9190
9200
9210
9220
9230
9240
9250
9260
9270
9280
9290
9300
9310
9320
9330
9340
9350
9360
9370
9380
9390
9400
9410
9420
9430
9440
9450
9460
9470
9480
9490
9500
9510
9520
9530
9540
9550
9560
9570
9580
9590
9600
9610
9620
9630
9640
9650
9660
9670
9680
9690
9700
9710
9720
9730
9740
9750
9760
9770
9780
9790
9800
9810
9820
9830
9840
9850
9860
9870
9880
9890
9900
9910
9920
9930
9940
9950
9960
9970
9980
9990
10000

middleware such as Tcl/Tk, Javascript, Perl, or the like etc., may run on top of the operating system, graphics and communication manager APIs for facilitating rapid development of these applications on the Wrist Watch device 10.

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5

The methodology of the present invention is to dynamically vary the number of minutes the minute hand moves forward per rotation event while tracking the latest direction in which the roller wheel is moving. If the current direction is the same as the previous direction and the minute hand is positioned so that the current minute indicated is a multiple of a predetermined number, e.g., five (5), the minute hand moves forward or back by five (5) minutes (depending on the direction of rolling). When the direction changes, the minute hand moves by single or (1) minute increments instead of five (5) minute increments, for example. Thus, in an example of setting watch hands 370, 372 to a value of 6:43AM, in order to move the minute hand from 0 to 43, from a position where the minute hand is currently at a twelve o'clock position, the user will first roll the wheel clockwise for five (5) clicks to go from 0 to 1 to 2 so on till five (5). Then, in the same direction, the user will roll the wheel clockwise for eight (8) more clicks to get the minute hand to forty-five (45), and then back (anti-clockwise) two (2) clicks to get to forty-three (43).

It is understood that variants of this method are possible. For example, instead of just using increments of 1 and 5, the steps may be dynamically increased, for instance, using steps of 1, 5 and 15. In this case, given the present example, the user will first roll for five (5) clicks to get to five (5). Then, in the same direction, the user will roll the wheel clockwise for two (2) more clicks in the same direction to get to fifteen (15) and then two (2) more clicks to get to forty-five (45). Then two clicks anti-clockwise to get to forty-three (43). In other words, when the rolling direction is unchanged and the minute hand hits a 15 minute boundary, the hand advances by 15 minutes; if it hits a 5 minute boundary (but not a 15 minute boundary), it advances by 5 minutes.

A related idea is to independently control the hour and minute hands and to switch the control of the roller from one to the other on a wheel click event. To set the time to 6:43 AM, the roller could first be controlling the hour hand, with each click moving the hand by 1 hour. Once the hour hand has been set to 6 AM, a roller wheel click event fixes the hour hand and now controls the minute hand which is set as described above with the dynamically varying interpretation of the roller clicks.

The detailed algorithm for providing dynamic speed scrolling of the minute hand in order to reduce the amount of user manipulation of the scroller to get to a particular position that the user wants to reach while retaining fine-grain control over positioning without needing excessive scroller manipulation, is as follows:

Forward Click

```

if { (lastdir == fwd) && (minute % 5) == 0 } {
    minute = minute + 5
} else {
    minute = minute + 1
}
if { minute >= 60 } {
    minute = minute - 60
    hour = (hour + 1) % 24
}
lastdir = fwd

```

Reverse Click

```

if { (lastdir == rev) && (minute % 5) == 0 } {
    minute = minute - 5
} else {
    minute = minute - 1
}
if { minute < 0 } {
    minute = minute + 60
    hour = (hour - 1 + 24) % 24
}
lastdir = rev

```

It is understood that the present invention may be used for other forms of scrolling where one needs fine control over a wide range. Dynamic scrolling may be used in any situation which benefits from fast movement and where any overshoot may be corrected quickly with small reverse steps. So this applies to scrolling through text, scrolling through horizontal time lines, spread sheets, moving past TV program listings, months in a calendar, etc..

Accordingly, a generalized version of the algorithm is as follows:

```

A: if (wheel_forward_signal) {
    if (last_wheel_signal = reverse) forward_movements = 0;
    forward_movements = forward_movements + 1;
    last_wheel_signal = forward;
B:  if (forward_movements > high_forward_threshold)
    scroll forward by high_forward_increment;
C:  else scroll forward by low_forward_increment;
D:  } else if (wheel_reverse_signal) {
    if (last_wheel_signal = forward) reverse_movements = 0;
    reverse_movements = reverse_movements + 1;
    last_wheel_signal = reverse;
E:  if (reverse_movements > high_reverse_threshold)
    scroll reverse by high_reverse_increment;
F:  else scroll reverse by low_reverse_increment;
    }

```

It is not necessary that the high_forward_increment equal the low_forward_increment though it may be desired to keep these values symmetric.

While the invention has been particularly shown and described with respect to illustrative and preformed embodiments thereof, it will be understood by those skilled in the art that the

YOR92000-0238